



No.	Name	Note	No.	Name	Note
1	Angle valve	1/4"Flare	17	Oil cooler connector(in)	3/4"Flare
2	Safety valve	1 1/4",option	18	Oil flow sight glass	
3	Discharge flange	4"	19	Earth bolt	M8
4	Economizer port	1 3/8", solder	20	Stop Pin	option
5	Solenoid valve	Stepless(NC or NO),option	21	Oil cooler connector(out)	3/4"Flare,option
6	Solenoid valve	25%(NC)	22	Suction flange	6"
7	Solenoid valve	50%(NC)	23	Angle valve	1/4"Flare
8	Solenoid valve	75%(NC),option	24	Oil drain valve	1/4"Flare
9	Check valve	4"	25	Discharge temp. sensor	110°C
10	Displacement indicator	Option	26	Refrigerant service valve	1/4"Flare
11	Oil or Liquid refrigerant injection connector	5/8"Flare	27	Cable box	Standard
12	Oil sight glass	High side	28	service flange	
13	Oil equalization valve	1/2"Flare,option	29	Oil heater	150W/300W
14	Oil pressure different switch	Connector, option			
15	Oil filter cartridge				
16	Oil level switch				

*All stop valve are optional

UNIT
SI: mm Imperial: (in)

Item	Date	Modification
△	2015.09.30	Error Correction
△	2014.08.21	There are 15 differences from 02 edition
△	2012.11.08	Dimension correction
△	2012.04.19	Delete1.Connector 2.Oil temp. sensor

Model	RC2-1020/1130A&B		
Name	Compressor outline		
			HANBELL NO. 04